



TECHNICAL DATA SHEET

HC 533

Polymer additive

General information

HC-533 is a polymer additive that, added to cement-based adhesives, fillers and used as primer, is an excellent gap, crack and eruption repairing agent. It improves the final strength, workability, and adhesion of most (not all) substances and makes them weather-proof, grindable and polishable.

Properties

- HC-533 significantly improves the general physical properties of grouts with cementitious binding agent.
- Solidifying effect, added to different substances, it increases solidity in varying degrees.
- De-sputtering.
- Quick and easy application.
- Grouts are passable and grindable in 12-24 hours after spreading.
- Soil humidity and other types of moisture can escape through the treated surface.

Application

With HTC Superfloor™:

- Various fillers may be used with the addition of HC-533 to repair noticeable gaps after deep sanding. In case of absorbent surfaces, it may be applied as primer with the help of a brush or a roller, diluted with water.
- In the case of the grouts we tested, ready corrections are grindable in 12-24 hours, if surface temperature reaches 15 °C.
- Application rate: 0.05 – 0.2 l/m² 1 layer, otherwise it depends on the type of repair.

Product description

Application: Depends on the type of use.

Appearance: Milky liquid.

Shelf life: 12 months

Packaging: In cans of 20 liters (in case of larger quantities it may be ordered in barrels or containers)

EPO – TREND Kft.

6800 Hódmezővásárhely,
Szántó Kovács János u. 114.



www.epo-trend.hu
megrendeles@epo-trend.hu

Office: +36 62 / 244 - 726

Additional information

Cleaning of tools: With water and soap.

Warning: Pay attention to hygiene when working with the product. Wash hands and clean every tool that came into contact with the product.

Storage:

- In a dry and cool location, in standing position.
- Protect from frost.
- Protect from open flames and excessive heat.
- Keep out of the reach of children.
- Close the can carefully after use.

Warranty: The efficient application of the product is the responsibility of the operator. The responsibility of the manufacturer is limited to the replacement of the product if it is proved to be substandard.

Distributor: Epo-trend Kft.